

NFRC Ratings - Thermal Aluminum 4000T Multislide

Glass values are based on Aluminum Spacer

Argon gas cannot be ordered for projects located above 4,000 ft. elevation; breather tubes required.

IGU Thickness	Grid	Glass Type	Pane 2	Pane 3	Gap 1	Gap 2	Fill	U_VALUE	SHGC	VT	CPD #
1" Dual Glazed	N	CLEAR	CLEAR		0.5		AIR	0.55	0.54	0.59	SOD-K-43-00029-00001
1" Dual Glazed	G	CLEAR	CLEAR		0.5		AIR	0.55	0.48	0.52	SOD-K-43-00029-00002
1" Dual Glazed	S	CLEAR	CLEAR		0.5		AIR	0.55	0.48	0.52	SOD-K-43-00029-00003
1" Dual Glazed	N	CLEAR	CLEAR		0.5		ARGON	0.54	0.54	0.59	SOD-K-43-00030-00001
1" Dual Glazed	G	CLEAR	CLEAR		0.5		ARGON	0.54	0.48	0.52	SOD-K-43-00030-00002
1" Dual Glazed	S	CLEAR	CLEAR		0.5		ARGON	0.54	0.48	0.52	SOD-K-43-00030-00003
1" Dual Glazed	N	Cardinal LoE-366	CLEAR		0.5		AIR	0.42	0.22	0.47	SOD-K-43-00015-00001
1" Dual Glazed	G	Cardinal LoE-366	CLEAR		0.5		AIR	0.42	0.20	0.41	SOD-K-43-00015-00002
1" Dual Glazed	S	Cardinal LoE-366	CLEAR		0.5		AIR	0.42	0.20	0.41	SOD-K-43-00015-00003
1" Dual Glazed	N	Cardinal LoE-366	CLEAR		0.5		ARGON	0.39	0.21	0.47	SOD-K-43-00016-00001
1" Dual Glazed	G	Cardinal LoE-366	CLEAR		0.5		ARGON	0.39	0.19	0.41	SOD-K-43-00016-00002
1" Dual Glazed	S	Cardinal LoE-366	CLEAR		0.5		ARGON	0.39	0.19	0.41	SOD-K-43-00016-00003
1" Dual Glazed	N	Cardinal LoE-366	i89		0.5		ARGON	0.35	0.21	0.46	SOD-K-43-00024-00001
1" Dual Glazed	G	Cardinal LoE-366	i89		0.5		ARGON	0.35	0.19	0.4	SOD-K-43-00024-00002
1" Dual Glazed	S	Cardinal LoE-366	i89		0.5		ARGON	0.35	0.19	0.4	SOD-K-43-00024-00003
1" Dual Glazed	N	Guardian LoE-SN68	CLEAR		0.5		AIR	0.43	0.29	0.51	SOD-K-43-00011-00001
1" Dual Glazed	G	Guardian LoE-SN68	CLEAR		0.5		AIR	0.43	0.26	0.44	SOD-K-43-00011-00002
1" Dual Glazed	S	Guardian LoE-SN68	CLEAR		0.5		AIR	0.43	0.26	0.44	SOD-K-43-00011-00003
1" Dual Glazed	N	Guardian LoE-SN68	CLEAR		0.5		ARGON	0.39	0.29	0.51	SOD-K-43-00012-00001
1" Dual Glazed	G	Guardian LoE-SN68	CLEAR		0.5		ARGON	0.39	0.26	0.44	SOD-K-43-00012-00002
1" Dual Glazed	S	Guardian LoE-SN68	CLEAR		0.5		ARGON	0.39	0.26	0.44	SOD-K-43-00012-00003
1" Dual Glazed	N	Guardian LoE-SN68	IS20		0.5		ARGON	0.36	0.28	0.5	SOD-K-43-00022-00001
1" Dual Glazed	G	Guardian LoE-SN68	IS20		0.5		ARGON	0.36	0.25	0.43	SOD-K-43-00022-00002
1" Dual Glazed	S	Guardian LoE-SN68	IS20		0.5		ARGON	0.36	0.25	0.43	SOD-K-43-00022-00003
1" Dual Glazed	N	Guardian LoE-62/27	CLEAR		0.5		AIR	0.42	0.21	0.46	SOD-K-43-00049-00001
1" Dual Glazed	G	Guardian LoE-62/27	CLEAR		0.5		AIR	0.42	0.19	0.4	SOD-K-43-00049-00002
1" Dual Glazed	S	Guardian LoE-62/27	CLEAR		0.5		AIR	0.42	0.19	0.4	SOD-K-43-00049-00003



NFRC Ratings - Thermal Aluminum 4000T Multislide

Glass values are based on Aluminum Spacer

Argon gas cannot be ordered for projects located above 4,000 ft. elevation; breather tubes required.

IGU Thickness	Grid	Glass Type	Pane 2	Pane 3	Gap 1	Gap 2	Fill	U_VALUE	SHGC	VT	CPD #
1" Dual Glazed	N	Guardian LoE-62/27	CLEAR		0.5		ARGON	0.39	0.21	0.46	SOD-K-43-00051-00001
1" Dual Glazed	G	Guardian LoE-62/27	CLEAR		0.5		ARGON	0.39	0.18	0.4	SOD-K-43-00051-00002
1" Dual Glazed	S	Guardian LoE-62/27	CLEAR		0.5		ARGON	0.39	0.18	0.4	SOD-K-43-00051-00003