arcadia CUSTOM
WINDOW AND DOOR SOLUTIONS
STEEL - ALUMINUM - WOOD

NFRC Ratings - Thermal Aluminum 3500T Sliding Door

Glass values are based on Stainless Steel Spacer

Argon gas cannot be ordered for projects located above 4,000 ft. elevation; breather tubes required.

IGU Thickness	Grid	Glass Type	Pane 2	Pane 3	Gap 1	Gap 2	Fill	U-VALUE	SHGC	VT	CPD #
1" Dual Glazed	N	Clear	Clear		0.5		Air	0.52	0.55	0.6	SOD-K-42-00053-00001
1" Dual Glazed	S	Clear	Clear		0.5		Air	0.61	0.49	0.53	SOD-K-42-00054-00001
1" Dual Glazed	N	Clear	Clear		0.5		Arg	0.51	0.55	0.6	SOD-K-42-00055-00001
1" Dual Glazed	S	Clear	Clear		0.5		Arg	0.60	0.49	0.53	SOD-K-42-00056-00001
1" Dual Glazed	N	Cardinal LoE 366	Clear		0.5		Air	0.39	0.22	0.48	SOD-K-42-00057-00001
1" Dual Glazed	S	Cardinal LoE 366	Clear		0.5		Air	0.51	0.20	0.42	SOD-K-42-00058-00001
1" Dual Glazed	N	Cardinal LoE366	Clear		0.5		Arg	0.35	0.21	0.48	SOD-K-42-00059-00001
1" Dual Glazed	S	Cardinal LoE366	Clear		0.5		Arg	0.48	0.19	0.42	SOD-K-42-00060-00001
1" Dual Glazed	N	Cardinal LoE366	i89		0.5		Air	0.34	0.21	0.47	SOD-K-42-00061-00001
1" Dual Glazed	S	Cardinal LoE366	i89		0.5		Air	0.41	0.19	0.41	SOD-K-42-00062-00001
1" Dual Glazed	N	Cardinal LoE366	i89		0.5		Arg	0.31	0.21	0.47	SOD-K-42-00063-00001
1" Dual Glazed	S	Cardinal LoE366	i89		0.5		Arg	0.39	0.19	0.41	SOD-K-42-00064-00001